

FD-115BMV & FD-118BMV



FEATURES

- High output bass-reflex cinema subwoofer
- Rated Power handling: 400 watts (FD-115BMV), 600 watts (FD-118BMV)
- Advanced 4-inch voice coil for earth-shaking low frequency
- Poplar plywood cabinet with matt black finish
- Perfect for general sound reinforcement applications in small and medium theatre

SPECIFICATION

System:

| | FD-115BMV | FD-118BMV |
|---------------------------|----------------------|----------------------|
| System Type: | Passive, Bass reflex | Passive, Bass reflex |
| Sensitivity: | 98dB, 2.83V @ 1m | 101dB, 2.83V @ 1m |
| Max. SPL | 127dB | 132dB |
| Frequency Range (-10 dB): | 30Hz – 1kHz | 28Hz – 500Hz |
| Rated Power Output : | 400W | 600W |
| Max. Power Output : | 800W | 1200W |
| Nominal Impedance: | 8 Ω | 8 Ω |
| Distortion | ≤1% | ≤1% |

Speaker:

| | | |
|-----------------------|-------------------------|-------------------------|
| LF Driver: | 15" x1, Paper diaphragm | 18" x1, Paper diaphragm |
| Driver Frame Material | Aluminium | Aluminium |
| Magnet: | 206x117x20 ferrite | 206x117x20 ferrite |
| Input connector | Barrier strip | Barrier strip |

Enclosure :

| | | |
|-----------------------------|---------------|---------------|
| Material: | 18 mm plywood | 18 mm plywood |
| Handle Quantity: | 2 | 2 |
| Finish: | Matt black | Matt black |
| Dimensions (L x W x H, mm): | 655*350*860 | 657*400*1014 |
| Weight (KG) | 43.5 | 53 |

*In an effort to continuously improve our product quality, specification and features mentioned above are subject to change without prior notice.