

FD-400MVP/500MVP



FEATURES

- Surround loudspeaker system for theatre
- 2 different size with powerful output for selection
- 1-inch titanium high-frequency compression driver with horn for even, full frequency coverage
- Lightweight ABS cabinet with wall mount bracket for easy installation and adjustment
- Perfect for both side and ceiling-surround of the latest digital sound formats



SPECIFICATION

System:	FD-400MVP	FD-500MVP
System Type:	Passive, two-way	Passive, two-way
Sensitivity:	100 dB, 2.83V @ 1m	101 dB, 2.83V @ 1m
Max. SPL	129dB	131dB
Frequency Range (-8 dB):	40Hz -20kHz	40Hz -20kHz
Rated Power Output :	400W	500W
Max. Power Output :	800W	1000W
Nominal Impedance:	8 Ω	8 Ω
Distortion	≤ 1%	≤ 1%
Speaker:		
HF Driver:	1.75' x1 , Ti diaphragm	1.75' x1 , Ti diaphragm
LF Driver:	12' x1, Paper diaphragm	12' x1, Paper diaphragm
Coverage Angle:	H100° x V80°	H100° x V80°
Crossover Frequency:	1.5kHz	2.2kHz
Enclosure :		
Material:	ABS cabinet	ABS cabinet
Grill:	PP +black cloth	PP +black cloth
Finish:	Matt black	Matt black
Dimensions (L x W x H,mm):	420*245*500	420*245*500
Weight (KG)	9.7	9.7

*In an effort to continuously improve our product quality, specification and features mentioned above are subject to change without prior notice.