

FD-1152MVN

FEATURES

- Two-way cinema loudspeaker system for small theatres
- 1 x 15" high power, 3" voice coil hyperventated woofers
- Rated Power handling: LF 300W, HF:50W continuous IEC pink noise
- 1.75" HF compression driver with a constant directivity horn for a perfect coverage of 90° x 40°
- Built-in latest precision transducers for accurated voice reproduction
- Poplar plywood cabinet with matt black PVC lamination
- Flat-front waveguide design for easy baffle wall installation



SPECIFICATION

System:

System Type:	Passive system, two-way
Sensitivity:	99 dB, 2.83V @ 1m
Max. SPL:	126dB
Frequency Range (-10 dB):	45Hz – 20kHz
Rated Power Output :	LF 300W, HF 50W (IEC standard)
Max. Power Output :	LF 600W, HF100W
Nominal Impedance:	8 Ω
Distortion	≤1%

Speaker:

HF Driver:	1.75" x1 , Ti diaphragm, Ferrite magnet
LF Driver:	15" x1, Paper diaphragm, Ferrite magnet
Coverage Angle:	H90° x V40°
Crossover Frequency:	LF/WF 1.5kHz

Enclosure :

Material:	15 mm plywood
Handles:	2
Finish:	Matt black textured finish
Dimensions (L x W x H):	LF: 650x300x1125 mm
Weight:	32 kg

*In an effort to continuously improve our product quality, specification and features mentioned above are subject to change without prior notice.