

FD-2152MVN

FEATURES

- High power, two-way bass reflex full range system
- 2 x 15" high power, 4" voice coil hypervented woofers
- Rated Power handling: 600W continuous IEC pink noise
- 3" HF titanium compression driver with a constant directivity horn for a perfect coverage of 90° x 40°
- Poplar plywood cabinet with matt black PVC lamination
- Flat-front waveguide design for easy baffle wall installation
- Ideals for small and medium theatres audio application



SPECIFICATION

System:

System Type:	FD-2152MVN Passive system, two-way
Sensitivity:	100 dB, 2.83V @ 1m
Max. SPL:	131dB
Frequency Range (-10 dB):	40 Hz – 16kHz
System Power Rating:	600W Continuous, 1200W Program
Nominal Impedance:	4 ±0.8 Ω
Distortion	≤1%

Speaker:

HF Driver:	3' x1 , Ti diaphragm, Ferrite magnet
LF Driver:	15' x2, Paper diaphragm, Ferrite magnet
Coverage Angle:	H90° x V40°
Crossover Frequency:	LF/WF 800Hz

Enclosure :

Material:	18 mm plywood
Handles:	2
Finish:	Matt black textured finish
Dimensions (L x W x H):	LF: 760x400 x830 mm M/HF: 760x347x 390 mm
Weight:	LF: 51 kg, M/HF:10.5 kg

*In an effort to continuously improve our product quality, specification and features mentioned above are subject to change without prior notice.