

FD-218BMV**FEATURES**

- Dual 18" drivers cinema subwoofer with usable response to 25 Hz (-10 dB)
- Rated Power handling: 1200W in IEC standard
- Bass-reflex enclosure for smooth response in a wide coverage
- Advanced 4-inch voice coil for earth-shaking low frequency
- Poplar plywood cabinet with matt black finish
- Perfect for general sound reinforcement applications in large theatre

SPECIFICATION**System:**

| | |
|---------------------------|----------------------|
| System Type: | Passive, Bass reflex |
| Sensitivity: | 102 dB, 2.83V @ 1m |
| Max. SPL | 136dB |
| Frequency Range (-10 dB): | 25Hz – 500Hz |
| Rated Power Output : | 1200W (IEC standard) |
| Max. Power Output : | 2400W |
| Nominal Impedance: | 8 Ω |
| Distortion | ≤1% |

Speaker:

| | |
|-----------------------|--------------------------|
| LF Driver: | 18' x2, Paper diaphragm |
| Driver Frame Material | Aluminium |
| Magnet: | 220 x 110 x 20mm Ferrite |
| Input connector | Barrier strip |

Enclosure :

| | |
|-------------------------|---------------------|
| Material: | 18 mm plywood |
| Handles: | 4 |
| Finish: | Matt black |
| Dimensions (L x W x H): | 1203 x 605 x 780 mm |
| Weight: | 100 kg |

*In an effort to continuously improve our product quality, specification and features mentioned above are subject to change without prior notice.