

## FD-08MVP/10MVP/12MVP



### FEATURES

- THX certified surround loudspeaker system for theatre
- 3 different size with powerful output for selection
- 1-inch titanium high-frequency compression driver with horn for even, full frequency coverage
- Lightweight ABS cabinet with wall mount bracket for easy installation and adjustment
- Perfect for both side and ceiling-surround applications of the latest digital sound formats



### SPECIFICATION

#### System:

	FD-08MVP	FD-10MVP	FD-12MVP
System Type:	Passive, two-way	Passive, two-way	Passive, two-way
Sensitivity:	93 dB, 2.83V @ 1m	96 dB, 2.83V @ 1m	97 dB, 2.83V @ 1m
Max. SPL	117dB	123dB	126dB
Frequency Range (-8 dB):	50Hz – 20kHz	50Hz – 20kHz	50Hz – 20kHz
Rated Power Output :	120W	200W	250W
Max. Power Output :	240W	400W	500W
Nominal Impedance:	8 Ω	8 Ω	8 Ω
Distortion	≤1%	≤1%	≤1%

#### Speaker:

HF Driver:	1' x1 , Ti diaphragm	1' x1 , Ti diaphragm	1' x1 , Ti diaphragm
LF Driver:	8' x1, Paper diaphragm	10' x1, Paper diaphragm	12' x1, Paper diaphragm
Coverage Angle:	H100° x V80°	H100° x V80°	H100° x V80°
Crossover Frequency:	2.5kHz	2.2kHz	2.2kHz

#### Enclosure :

Material:	ABS cabinet	ABS cabinet	ABS cabinet
Grill:	PP +black cloth	PP +black cloth	PP +black cloth
Finish:	Matt black	Matt black	Matt black
Dimensions (L x W x H,mm):	330x227x430	420*245*500	450*273*540
Weight (KG)	7	8	11

\*In an effort to continuously improve our product quality, specification and features mentioned above are subject to change without prior notice.